

FDH BRASS

ISO 9001 : 2000





F501 This valve is ideal for hydro, heating and pneumatic plants.

- 1/2" to 2" in hot pressed brass
- 2-1/2" to 4" in casting brass
- Seals in Metal
- Max. working temperature=110°C
- Opening pressure = 0.03 bar
- Thread end : BSP

DIMENSIONS

BAR:MAX	16	16	16	10	10	10	8	8	8
G	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3	4
L	47	53	63	70	88	97	120	135	162
H	48.5	56.5	63.5	78	98	109	130	145	180
WEIGHT(g)	180	240	350	550	880	1200	1780	2900	5000




F503 Brass filter suitable for heating, sanitary and hydro plants, used for water, steam, air and oils.

- 1/2" to 2" in hot pressed brass
- 2 1/2" to 4" in casting brass
- Sieve in stainless steel AISI 304
- Standard production 50 mesh.
- Max. working temperature=110°C
- Thread end : BSP

DIMENSIONS

BAR:MAX	16	16	16	10	10	10	8	8	8
G	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3	4
L	55	68	75	96	105	125	146	170	210
H	40	48	50	68	70	90	105	125	155
WEIGHT(g)	130	200	280	560	680	1250	2650	3000	6200



F601 This valve is ideal for sanitary and watering plants.

- Body in hot pressed brass
- Wheel in iron
- Bonnet in brass
- Packing nut in brass
- Stem in brass
- Baffle in brass
- Bonnet washer in fiber
- Stem washer in Teflon
- Thread end : BSP

DIMENSIONS

BAR:MAX	16	16	16	10	10	10	8	8	8
G	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3	4
L	38	41	44	50	51	60	60	74	85
H	50	50	60	60	70	70	90	100	120
WEIGHT(g)	165	200	270	430	565	955	1800	2500	4200

