

FDH BRASS ISO 9001 : 2000


Spring Check Valve



F201

This valve is ideal for all types of plants : hydraulic, pneumatic and heating plants. It is suitable to install in horizontal, vertical or oblique position.

- Body in hot pressed brass bar
- Seals in NBR-rubber
- Spring in stainless steel AISI 304
- Washerholder in Nylon
- Max working temperature=110°C
- Opening pressure = 0.03 bar
- Thread end : BSP



DIMENSIONS

BAR:MAX	16	16	16	10	10	10	8	8	8
G	1.2"	3.4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"
D	33	42	47.5	59	67.5	81	103	111	140.5
H	45	48	56	61	68	77	93	95	107
WEIGHT(g)	120	180	240	330	500	700	1550	1900	3100

Foot Valve




F401

This valve is suitable for industrial, pneumatic and hydraulic installations. And ideal for hot/cold water, different oils and compressed air. It can be fitted in horizontal, vertical or oblique position.

- Body in hot pressed brass bar
- Seals in NBR-rubber
- Spring in stainless steel AISI 304
- Washerholder in Nylon
- Filter threaded end : Nylon
- Filter mesh in stainless steel AISI 304
- 1200 micron from 1/2" up to 2"
- 2000 micron from 2-1/2" up to 4"

- Max working temperature=110°C
- Opening pressure = 0.03 bar
- Thread end : BSP



DIMENSIONS

BAR:MAX	16	16	16	10	10	10	8	8	8
G	1.2"	3.4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"
D	33	42	47.5	59	67.5	81	103	111	140.5
H	66	72	85.5	95.5	112	140	158	167	192
WEIGH	80	120	160	230	315	490	110	1230	1860